


Operator
Telephone
Fax
e-Mail

Exterior Scene 1 / Sport Luminaires (Coordinates List)



Scale 1 : 1533









List of the Sport Luminaires

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
[Redacted] White 4000K LED CRI70 1200mA - A6 Optic	1	-36.735	-36.302	18.500	6.979	-16.011	0.000	21.0	(C IMax, G IMax)	/
[Redacted] White 4000K LED CRI70 1200mA - A6 Optic	2	-39.666	-36.254	18.500	-46.187	1.112	0.000	26.0	(C IMax, G IMax)	/
[Redacted] White 4000K LED CRI70 1200mA - A6 Optic	3	39.341	-34.963	18.500	-5.918	-18.401	0.000	21.0	(C IMax, G IMax)	/
[Redacted] White 4000K LED CRI70 1200mA - A6 Optic	4	-37.350	32.993	18.500	6.293	12.549	0.000	21.0	(C IMax, G IMax)	/

Operator
Telephone
Fax
e-Mail

Exterior Scene 1 / Sport Luminaires (Coordinates List)

List of the Sport Luminaires

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
 4000K LED CRI70 1200mA - A6 Optic	5	52.184	32.708	18.500	8.469	12.416	0.000	21.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	6	42.341	-34.963	18.500	45.713	2.817	0.000	26.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	7	-40.350	32.993	18.500	-47.002	-4.350	0.000	26.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	8	54.305	30.587	18.500	41.270	-5.034	0.000	26.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	9	-0.964	-34.821	18.500	-35.042	-0.743	0.000	21.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	10	2.036	-34.821	18.500	36.114	-0.743	0.000	21.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	11	-8.206	32.463	18.500	-39.185	-4.456	0.000	21.0	(C IMax, G IMax)	/
 4000K LED CRI70 1200mA - A6 Optic	12	-5.206	32.463	18.500	34.272	4.820	0.000	21.0	(C IMax, G IMax)	/